

# BESSEL

BESSEL returns the Bessel function value for a numerical expression, based on the indicated order.

## Syntax

BESSEL(FunctionType\$, NumExp)

### Arguments

- **FunctionType\$** is a string expression that indicates the order of the Bessel function:
  - a. "I1", Modified Bessel function of the first kind;
  - b. "J1", Bessel function of the first kind, first order;
  - c. "Y1", Bessel function of the second kind, first order;
  - d. "K1", Modified Bessel function of the second kind;
- **NumExp** is a numerical expression

## Remarks

1. Information on the Bessel function and its orders can be found [here](#) (Wikipedia).

## Examples

### Method 1

Modified Bessel function of the first kind;

BESSEL("I1", 0.3) returns 0.15169383946249

---

### Method 2

Bessel function, first kind, first order:

BESSEL("J1", 0.3) returns 0.14831881628779

---

### Method 3

Bessel function, second kind, first order:

BESSEL("Y1", 0.3) returns -2.29310513710031

---

### Method 4

Bessel function, second kind, first order:

BESSEL("K1", 0.3) returns 3.05599204051877

---

## Example knowledgebases

### Download

An example knowledgebase of this function can be downloaded [here](#).

### Description

#### Input

A is the input value, B1, B2, B3, B4 are the four alternative BESSEL functions.

---

Quick links: [Functions overview](#) | [Attribute overview](#) | [Constants overview](#) | [Dimensions overview](#)