

# SECTION\$

**SECTION\$** returns a section from a document starting and ending with lines containing specific strings

## Syntax

**SECTION\$(Document\$, PageHeader\$, PageEnd\$, [AddLines%=>0])**

### Arguments

- Document\$ is a string containing the source document.
- PageHeader\$ is a sub string of Document\$ which indicates the first line of the section.
- PageEnd\$ is a sub string of Document\$ that indicates the end of the section.  
The result starts with the first line of Document\$ containing PageHeader\$ and ends with the line just before the line containing PageEnd\$.
- AddLines% is an optional value, containing the number of lines to be added at the end of the section. E.g. when AddLines%=1, also the line containing PageEnd\$ is included.

## Remarks

1. If PageHeader\$="NullString", the function returns "NullString".
2. If PageHeader\$ is not found, the function also returns "NullString".
3. If PageEnd\$="NullString", the function returns all text from Document starting with PageHeader\$.
4. If PageEnd\$ is not found, the function also returns all text from Document starting with PageHeader\$.
5. The last line of the result returned by **SECTION\$()** is always terminated by a **CrLf** (Carriage Return + LineFeed: **Chr\$(13)+Chr\$(10)**). Multiple repeating **CrLf**'s at the end of an extracted section are removed as well as trailing strings from each line in that result.
6. One can also use the **PARAGRAPHS** function to return a section of a document.

## Examples

Assuming a document with the following text:

```
"Turning and turning in the widening gyre
The falcon cannot hear the falconer;
Things fall apart; the centre cannot hold;
Mere anarchy is loosed upon the world
The blood-dimmed tide is loosed, and everywhere
The ceremony of innocence is drowned;
The best lack all conviction, while the worst
Are full of passionate intensity"
```

then

```
SECTION$(Document$, "fall apart", "ceremony")
```

returns

```
"Things fall apart; the centre cannot hold;
Mere anarchy is loosed upon the world
The blood-dimmed tide is loosed, and everywhere
"
```

---

```
SECTION$(Document$, "fall apart", "Ceremony")
```

returns

```
"Things fall apart; the centre cannot hold;
Mere anarchy is loosed upon the world
The blood-dimmed tide is loosed, and everywhere
The ceremony of innocence is drowned;
The best lack all conviction, while the worst
Are full of passionate intensity
"
```

Because "Ceremony" does not occur in Document\$. Note, the function is case sensitive.

---

```
SECTION$(Document$, "falls apart", "ceremony")
```

returns

"NullString"

since "falls apart" is not present in Document\$.

---

SECTION\$(Document\$, "fall apart", "ceremony", 2)

returns

"Things fall apart; the centre cannot hold;  
Mere anarchy is loosed upon the world  
The blood-dimmed tide is loosed, and everywhere  
The ceremony of innocence is drowned;  
The best lack all conviction, while the worst

"

Two more lines are included.

---

Quick links: [Functions overview](#) | [Attribute overview](#) | [Constants overview](#) | [Dimensions overview](#)